





## 720P AHD Colour Mobile Box Camera

Model: **AC 5881 AHD**

Analog AHD, 1.3Mega Pixel, 12V DC



### Dimensions:



### Features:

- Metal-cased mobile box with fixed lens.
- Available in black finish.
- Low power consumption.
- Easy installation on ceiling or wall, surface or flush mount.
- IP67 waterproof.


### Packing list:

|                     |   |
|---------------------|---|
| Camera              | 1 |
| Instruction Manual  | 1 |
| Self Drilling Screw | 2 |
| Hex-key             | 1 |

### Operation procedures:

1. Loosen the lock screws on the sun shield, remove the mounting bracket to the suitable position.
2. Attach the mounting bracket to the wall or ceiling, wherever you want to install the camera. Locate a wall stud or ceiling joint and secure the base by the supplied mounting screws.
3. Connect the cable to DC12V power input and video output.
4. Fix the lock screw.

### Cable Connection:



- 1---12VDC (+)
- 2---12VDC/GND (-)
- 3---N/A
- 4---Video

### Specifications:

| Model                   | AC 5881 AHD               |
|-------------------------|---------------------------|
| Pick up Device          | 1/3" CMOS AR0130          |
| TV System               | PAL/NTSC (Optional)       |
| Picture Elements        | 1280 (H) x 960 (V)        |
| Sensitivity             | 0 Lux (IR LED On)         |
| Scanning System         | Progressive scan RGB CMOS |
| Synchronization         | Internal                  |
| S/N Ratio               | More than 44dB(AGC Off)   |
| Auto Gain Control (AGC) | Auto                      |
| Electronic Shutter      | Auto                      |
| Back Light Compensation | Auto                      |
| Infrared Spectrum       | 850 nm                    |
| Infrared LED            | 18 LEDs                   |
| Mirror                  | Available                 |
| ICR                     | Available                 |
| Noise Reduction         | 3D                        |
| Dynamic range           | 83.5 dB                   |
| Video Output            | 1 Vp-p, 75Ω,AHD           |
| Audio Output            | Optional                  |
| Lens                    | f2.8mm Megapixel          |
| Pan Adjusting           | N/A                       |
| Tilt Adjusting          | 0-60 Degree               |
| Power Supply            | 9-18V DC                  |
| Power Consumption       | 180mA                     |
| Dimensions (L X W X H)  | L69 x W76 x H78 mm        |
| Net Weight              | 285g                      |
| Weatherproof            | IP67                      |
| Operating Temperature   | -30~ +70 ° C              |

\*Specifications are subject to change without prior notice.